

## 2.3 Contract Gloss



### DESCRIPTION

Leyland Contract Gloss is specially formulated to provide a high gloss finish to wood and metal surfaces. The outstanding opacity, brilliant whiteness and excellent application properties make it ideal for interior and exterior new work application.

### Recommended uses

Interior ✓ Exterior ✓

### Type of substrate

Wood and metal.

### Colour range

Brilliant White.

### Finish

Gloss

### Volume solid

60%

### Coverage

Leyland Contract Gloss will cover approximately 17 square metres per litre depending on the nature and porosity of the surface.

### Drying time

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.  
STORE AWAY FROM HEAT AND FLAME.

### Cleaner

White Spirit.

### VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400 g/l (2007) / 300 g/l (2010). This product contains max 300 g/l VOC.

### Film thickness

Wet: 60µm

Dry: 36µm

### Preparation

All surfaces to be painted should be clean, dry and free from grease. Loose, flaking or blistered paint should be completely removed. Prime all new and bare surfaces with the appropriate Leyland Primer followed by Leyland Undercoat. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

### Application

Stir well before use. Apply by brush or roller. The brush should be fully loaded for best results. Apply one or more coats as required and allow 16-24 hours between coats under normal conditions.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with white spirit or turpentine substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### Precautions

PAINT PRODUCT  
FLAMMABLE

- Contains Cobalt bis(2-ethylhexanoate) and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition - No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- Restrict interior use to small surface areas such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas – walls, floors or ceilings – or in confined spaces.
- If swallowed, seek medical advice immediately and show this container.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS Safety data sheet available on request.  
Manufactured under a quality system approved by the BSI.