

1.12 Satinwood



DESCRIPTION

A hard wearing, knock-resisting, satin finish which is self-undercoating and easy to use on interior wood and metalwork.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Wood and metal.

Colour range

Brilliant White.

Finish

Satin

Volume solid

56%

Coverage

1 litre will cover approximately 20 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.
STORE AWAY FROM HEAT AND FLAME.

Cleaner

White Spirit.

VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400 g/l (2007).
This product contains max 400 g/l VOC.

Film thickness

Wet: 50µm

Dry: 28µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Prime all new and bare surfaces with the appropriate Leyland primer. Rub down sound previously painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Apply evenly by brush or roller and avoid overspreading. Apply one or more coats as required and allow 16-24 hours drying between coats under normal conditions. Do not apply over polystyrene surfaces.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Precautions

PAINT PRODUCT
FLAMMABLE

- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- Restrict interior use to small surface areas such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas – walls, floors or ceilings – or in confined spaces.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS Safety data sheet available on request.
Manufactured under a quality system approved by the BSI.