

Multi-Surface Primer Undercoat

Leyland Trade Multi-Surface Primer Undercoat is a water based preparation coat for use with all Leyland Trade top coats including Leyland Trade Multi-Surface Paint. It can be used on many different interior and exterior surfaces including; walls, wood, masonry, metal, plaster, wallboard, concrete, cement rendering, brickwork and blockwork, galvanised steel, tile and kitchen cupboards (melamine). It features good stain blocking properties to resist day-to-day stains from bleeding through the paint film.

Recommended uses

Interior ✓

Type of substrate

For use on many different interior and exterior surfaces including; walls, wood, masonry, metal, plaster, wallboard, concrete, cement rendering, brickwork and blockwork, galvanised steel, tile and kitchen cupboards (melamine). For further advice on other substrates contact Technical Advisory.

Colour availability

Brilliant White

Finish

N/A

Volume solid

45%

Coverage

Leyland Trade Multi-Surface Primer Undercoat will cover approximately 8 -10 square metres per litre depending on the nature and porosity of the surface being painted.

Drying time

Touch dry in 30 minutes. Recoatable after 3-4 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

Film thickness

Wet: 100 µm
Dry: 45 µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Rub down previously painted surfaces with fine waterproof abrasive to provide a good key. Hard wall plasters should be scored with coarse glasspaper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For further advice contact Technical Advisory on 01924 354354 or visit www.leylandtrade.com

Application

Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use. Apply one full coat, brushing firmly into the surface. Porous surfaces should be sealed with a first coat of Leyland Trade Multi-Surface Primer Undercoat thinned with up to 20% clean water. Allow 3 hours to dry under normal conditions before applying the required paint finish. For best results, apply by brush as this assists the primer to penetrate the surface. Allow fresh plaster to dry thoroughly before application. Do not apply when air or surface temperature is below 10°C.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm, soapy water and rinse thoroughly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354