

## Fast Drying Water Based Satin

Leyland Fast Drying Satin is a premium quality, high opacity paint specially developed to produce a tough satin sheen finish that dries quickly. Suitable for interior and exterior wood and metal, the non yellowing formula benefits from excellent flow and is both fast drying and low odour ensuring easy application and minimal downtime.

### Recommended uses

Interior ✓ Exterior ✓

### Type of substrate

Wood and metal.

### Colour availability

Brilliant White and Black (2.5ltr & 750ml).  
Thousands of tinted colours also available  
(2.5ltr)

### Finish

Satin

### Volume solid

35%

### Coverage

1 litre will cover approximately 15 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one can of a colour in the same room, intermix before use.

### Drying time

Recoat after 3-4 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.  
PROTECT FROM FROST.

### Film thickness

Wet: 80µm  
Dry: 28µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down sound previously gloss painted surfaces with fine waterproof abrasive paper to provide a key and rinse thoroughly before applying a pre-coat of Leyland Trade Fast Drying Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply Knotting Solution to knots and resinous surfaces and prime exposed wood and metal surfaces with the appropriate Leyland Primer. Special precautions should be taken during the surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

### Application

Stir well before use. Apply by brush or roller. Apply liberally and evenly for a smooth finish. Under normal conditions, allow 4 hours before applying a second coat if required. Do not apply when air or surface temperature is below 10°C or externally when rain is imminent.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: [www.leylandtrade.com](http://www.leylandtrade.com) or call 01924 354354