

1.15 Wood Primer



DESCRIPTION

Leyland Wood Primer is suitable for use on bare interior and exterior timber surfaces, providing excellent adhesion.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Softwood and non-oily hardwood.

Colour range

White.

Finish

N/A

Volume solid

59%

Coverage

1 litre will cover approximately 12 square metres depending on the nature and porosity of the surface.

Drying time

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.

STORE AWAY FROM HEAT AND FLAME.

Cleaner

White Spirit.

VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400 g/l (2007).

This product contains max 400 g/l VOC.

Film thickness

Wet: 83µm

Dry: 49µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down the bare timber surfaces with dry glasspaper to remove raised grain and sharp edges. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply Knotting Solution to knots and resinous areas, and allow to dry thoroughly. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Suitable for application by brush or roller. Apply liberally, working firmly into the surface and laying off in the line of the grain. Take care to treat all accessible timber particularly the end grain. Allow to dry thoroughly before applying the relevant undercoat and finishing paint.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Precautions

PAINT PRODUCT

FLAMMABLE

- Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- Restrict interior use to small surface areas such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas – walls, floors or ceilings – or in confined spaces.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS Safety data sheet available on request.

Manufactured under a quality system approved by the BSI.